

Avery Dennison Pathfinder® 6057 Printer

Product Specifications

- Handheld Programmable Printer
Integrated with Optional Scanner
- One Piece Ergonomics – Scan, Print and Apply
- Windows Operating System and Touch Screen Display
- Thermal Direct
- Prints Receipts, Tags and Labels



Standard Features

Dimensions:

Height – 9.84" (250 mm)
Width – 8.25" (209 mm)
Depth – 3.00" (76 mm)
Weight – 1.94 lbs. (.88 kg)
Shipping Wt. – 5.5 lbs. (2.52 kg)

Printing Method:

Thermal Direct

Printhead:

1.89" (48 mm)
203 dots/inch (8 dots/mm)

Keypad/Display:

Virtual Keyboard on Display. Three Software Controlled Contextual Keys, Off/On, Trigger, 1/2VGA (320 x 480 pixel) VGA color graphics LCD with touchscreen

Memory:

128 MB RAM, 256 MB Flash
Optional Micro SD memory card

Operating System:

Microsoft® Windows CE .NET Version 6.0 R3

Communications:

USB port
Optional Symbol 802.11b/g radio cards
Bluetooth

Bar Code Types:

UPCA +2/+5, UPCE +2/+5, EAN8 +2/+5, EAN13 +2/+5, Interleaved 2 of 5, Code 16k, Codabar (NW7),

Code 128, Code 39, MSI, PDF417, Code 93, Postnet, Maxicode and QR Code

Standard Fonts:

TrueType® & International

Font Magnification:

4 to 200 pt. for scalable/TrueType fonts

Printer Warranty:

One (1) year parts and labor (ship-in).
Full written warranty statement is available on request

Printhead Warranty:

Six (6) months, or one million inches (1,000,000"),
whichever occurs first

Battery and Cable Warranty:

Three (3) Months pro-rated from date of shipment.
Physical damage to the batteries or cables will not be covered by the limited warranty

Supplies


Only Monarch® supplies are recommended. For high density and serial bar codes, Monarch "premium" supplies are recommended. The printer supports die cut, black mark, and non-indexed supplies.

Supply Types:

Tags, Labels, and Receipt Paper

Supply Sizes:

Width – 1.1" up to 2.0" (28 mm to 51 mm)
Length - .55" to 8.0" (14 mm to 203 mm)
Supply Roll lengths – 420" to 580" (10.7 to 14.7 meters)
Custom lengths are available.



Avery Dennison Pathfinder® 6057 Printer

Product Specifications

Monarch®
Products and Services

Environmental Ranges

Operating Temperature:

41° to 104° F (5° to 40° C)

Storage:

-4° to 122° F (-20° to 50° C)

Humidity/Operating and Storage:

5% to 90% non-condensing

Electrostatic Discharge and Air Quality:

Some issues with electronic equipment may occur in environments prone to static discharge or extreme dust conditions. Avery Dennison suggests that you take precautions to minimize these issues.

Performance

Power Source:

Monarch® 7.4V Lithium Ion Battery Pack

Print Speed: Up to 5 ips (127 mm/sec)

Print Ratio:

30% black maximum per square inch

Inches Per Charge:

Up to 3,000" (76 meters) of 30% black printing on the supply. Factors such as scanning, use of LAN Radios and duty cycle can reduce inches printed per charge.

Battery Cycle Life:

Approximately 300 full discharge cycles. Many factors effect individual battery performance.

Recommended Duty Cycle:

33% Duty Cycle for continuous printing (5 minutes out of 15 minutes time intervals). On-demand or intermittent printing has no restrictions.

Options

- Integrated Laser Scanner
- 802.11 b/g Radio Cards
- Micro SD Memory Cards

Accessories

- Battery (part#12009502)
- 9465™ Four Station Battery Charger
- 9462™ Single Station Battery Charger
- Deluxe Hand Strap (part#124053)
- USB Cable
- 6055/6054 Communication/Charging/Docking Station
- Shoulder Strap (part# 127333)
- Deluxe Padded Wrist Strap (part# 126791)

In our ongoing effort to deliver the best technology, specifications are subject to change without notice.



Avery Dennison Retail Branding and Information Solutions

170 Monarch Lane Miamisburg, OH 45342

1.800.543.6650 Monday-Friday, 8 AM–6:30 PM ET

www.monarch.averydennison.com



Retail Branding and
Information Solutions